

Finished Size: 58" x 61"



21603 B



21437 JG



21434 B



21435 T



21439 E



21438 T



21440 E



21433 E

YARDAGE REQUIREMENTS

Design	Yards
21603 B	¾
21437 JG	1 ¼
21434 B	1¼
21435 T	½
21439 E	½
21438 T	1
21440 E	1
21433 E	1 Panel
21436 KG (backing)	4

Designed by: Tammy Silvers and Julia LaBauve of Outside the Line Designs. www.OTLDesigns.com

Note: Unless noted, measurements are given in inches and seam allowance is $\frac{1}{4}$ ". Strips are cut selvedge to selvedge unless otherwise noted.

MATERIALS NEEDED:

- $\frac{3}{4}$ yard water 21603 B
- $\frac{1}{4}$ yard trees 21437 JG
- $\frac{1}{4}$ yard border 21434 B
- $\frac{1}{2}$ yard buildings 21435 T
- $\frac{1}{2}$ yard white 21439 E
- 1 yard brown 21438 T
- 1 yard stripes 21440 E
- 1 panel 21433 E
- 66" x 69" piece of batting
- 4 yards backing fabric

CUTTING:

1. Water: cut (5) $3\frac{1}{2}$ " strips. Sub cut into (4) $3\frac{1}{2}$ " x 45" strips.
2. Trees:
 - a. Cut (5) $3\frac{1}{2}$ " strips. Sub cut into (4) $3\frac{1}{2}$ " x 45" strips.
 - b. Cut (6) $2\frac{1}{4}$ " binding strips.
 - c. Cut (1) 2" strip. Sub cut into (16) 2" squares.
3. Border: from each of the motifs, water, park, and street, cut (1) $4\frac{1}{2}$ " x 45" strip. Note that these stripes run parallel to the selvedge.
4. Buildings: cut (2) $4\frac{1}{2}$ " strips. Sew the strips together along the $4\frac{1}{2}$ " side, making sure that the motifs match at the seam. From this long strip cut (1) $4\frac{1}{2}$ " x 45" motif strip.
5. White: cut (9) $1\frac{1}{2}$ " strips. Sew the strips together. Sub cut into (8) $1\frac{1}{2}$ " x 45" strips.
6. Brown:
 - a. Cut (6) $2\frac{1}{2}$ " strips. Sub cut into (2) $2\frac{1}{2}$ " x 53" inner side borders and (2) $2\frac{1}{2}$ " x 54" inner top/bottom borders.
 - b. Cut (4) $1\frac{1}{2}$ " strips. Sub cut into (3) $1\frac{1}{2}$ " x 50" long sashing strips.
 - c. Cut (4) 2" strips. Sub cut into (16) 2" x $9\frac{1}{2}$ " block sashing strips.
7. Stripes: cut (6) $3\frac{1}{2}$ " strips. Sub cut into (2) $3\frac{1}{2}$ " x 57" strips and (2) $3\frac{1}{2}$ " x 60" strips.
8. Panel: cut out each of the 4 city blocks. Trim each one down to $9\frac{1}{2}$ " square.

SEWING:



9. Sew a 2" tree square to either side of a 2" x $9\frac{1}{2}$ " block sashing strips. Press to the sashing. Repeat to make a total of 8 pieced sashing strips.

10. Sew a 2" x $9\frac{1}{2}$ " sashing strip to either side of a city block. Press to the sashing. Repeat with all city blocks.

11. Sew a pieced sashing strip to the top and another to the bottom of the city block. Press away from the city block.



12. Sew a $1\frac{1}{2}$ " x 45" white strip to the top and one to the bottom of each of the motif strips (water, park, street, and buildings).

13. Sew a $1\frac{1}{2}$ " x 45" tree strip to the top and one to the bottom of the street and building motif strips.



14. Sew a $1\frac{1}{2}$ " x 45" water strip to the top and one to the bottom of the water and park motif strips.

15. Trim the street and the water strips down to $3\frac{1}{2}$ " long.


16. Sew the street strip to the right of the block.

17. Sew the water strip to the left of the block.

18. From the building strip, cut (1) $12\frac{1}{2}$ " long segment and (1) $24\frac{1}{2}$ " long segment.

19. From the park strip, cut (1) $12\frac{1}{2}$ " long segment and (1) $24\frac{1}{2}$ " long segment.

20. Sew the $12\frac{1}{2}$ " water segment to the left of the block. Sew the $24\frac{1}{2}$ " segment to the right of the block.




21. Sew the $24\frac{1}{2}$ " building segment to the left of the block. Sew the $12\frac{1}{2}$ " segment to the right of the block.


22. Following the quilt diagram, lay out the rows and long sashing strips.



23. Sew a long sashing strip to the bottom of the street row. Repeat with the park and the buildings rows.
24. Sew the rows together.



25. Sew the side inner borders.



26. Sew the top/bottom inner borders.



27. Repeat with the outer borders.

FINISH THE QUILT

28. Cut the backing fabric into (2) 2 yards long pieces.
29. Using a $\frac{1}{4}$ " – $\frac{1}{2}$ " seam allowance, sew the two pieces of backing fabric together, along the long side. Press the seam open.
30. Center and lay the batting on top of the wrong side of the backing fabric
31. Center and lay the pieced quilt top on top of the batting.
32. Pin or baste the quilt sandwich using your preferred method for securing layers.
33. Quilt as desired.

While all possible care has been taken to ensure the accuracy of this pattern, we are not responsible for printing errors or the way in which individual work varies.